

Package: fahb (via r-universe)

June 4, 2026

Title Design and Analysis of Pilot Trials Assessing Recruitment Feasibility

Version 1.0.0.9000

Description Find optimal decisions rules for guiding progression decisions following a pilot trial, assuming a hierarchical recruitment model. Estimate the time until the main trial recruits to target, given the recruitment data observed in the pilot.

License MIT + file LICENSE

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.3

Suggests BH, knitr, patchwork, RcppEigen, rmarkdown, testthat (>= 3.0.0)

Config/testthat/edition 3

Imports brms, ggplot2, mco, mgcv, posterior, rlang

VignetteBuilder knitr

URL <https://dtwilson.github.io/fahb/>, <https://github.com/DTWilson/fahb>

BugReports <https://github.com/DTWilson/fahb/issues>

Config/pak/sysreqs make libicu-dev

Repository <https://lictr.r-universe.dev>

Date/Publication 2026-05-05 13:52:30 UTC

RemoteUrl <https://github.com/lictr/fahb>

RemoteRef HEAD

RemoteSha d3e0efe0e9ade882554125d17a64941857a8a5a3

Contents

check_priors	2
fahb_analysis	3
fahb_design	4
fahb_problem	4
forecast	5
plot.fahb_analysis	6
plot.fahb_design	6
print.fahb_analysis	7
print.fahb_design	7
Index	9

check_priors	<i>Plot prior distributions</i>
--------------	---------------------------------

Description

Given the hyperparameters encoded in a `fahb_problem` object, return plots of the three prior distributions and a plot of the prior predictive distribution of the recruitment rate at a randomly selected site.

Usage

```
check_priors(problem)
```

Arguments

`problem` an object of class `fahb_problem`.

Value

a list of `ggplot2` plots.

Examples

```
problem <- fahb_problem()
check_priors(problem)
```

fahb_analysis *Build a fahb analysis object*

Description

Given a `fahb_problem` object calculate summary statistics which can inform progression decisions. These include both standard progression criteria statistics, and the expectation of the posterior predictive distribution of the time until the trial recruits.

Usage

```
fahb_analysis(n_pilot, t_pilot, problem, site_t = NULL, bayes_model = NULL)
```

Arguments

<code>n_pilot</code>	integer vector of numbers recruited at each open site.
<code>t_pilot</code>	numeric vector of time (in years) each site has been open.
<code>problem</code>	object of class <code>fahb_problem</code> .
<code>site_t</code>	In the case of an external pilot, the time taken for all pilot sites to open.
<code>bayes_model</code>	optional object of class <code>brmsfit</code> which will be used in the Bayesian analysis via <code>brms::update()</code> to avoid compiling a new model.

Value

An object of class `fahb_analysis`.

Examples

```
## Example illustrating a full analysis workflow  
## (Not run on CRAN due to Bayesian model fitting)
```

```
problem <- fahb_problem()  
problem <- forecast(problem)
```

```
## Pilot trial data  
n_pilot <- c(3, 5, 2)  
t_pilot <- c(0.5, 0.6, 0.4)
```

```
analysis <- fahb_analysis(  
  n_pilot = n_pilot,  
  t_pilot = t_pilot,  
  problem = problem  
)
```

```
print(analysis)  
plot(analysis)
```

fahb_design *Build a fahb design object*

Description

Given a fahb_problem object, find efficient progression decision rules. These can include rules of the standard "progression criteria form", or rules based on a Bayesian analysis of the pilot trial data, or both.

Usage

```
fahb_design(problem, quietly = TRUE)
```

Arguments

problem	an object of class fahb_problem.
quietly	if this argument is set to FALSE then information about which steps have been completed will be printed to the console. Defaults to TRUE.

Value

an object of class fahb_design.

Examples

```
problem <- forecast(fahb_problem(), n_sims = 500)
fahb_design(problem)
```

fahb_problem *Build a fahb_problem object*

Description

Given a trial design and a set of model hyperparameters, build an object of class fahb_problem.

Usage

```
fahb_problem(
  N = 320,
  m = 20,
  t = 0.5,
  n_ext = NULL,
  m_ext = NULL,
  rel_thr = 1.2,
  so_hps = c(30, 2.85),
```

```

    mean_rr_hps = c(2, 0.329),
    sd_rr_hps = c(30, 100)
  )

```

Arguments

N	target sample size.
m	number of recruiting sites.
t	timing of the pilot analysis in years.
n_ext	number of participants to recruit to an external pilot.
m_ext	number of sites to open in an external pilot.
rel_thr	threshold which discriminates feasible and infeasible trials, as a multiple of the expected time to recruit.
so_hps	site opening rate hyperparameters (shape and rate for a Gamma prior).
mean_rr_hps	mean site recruitment rate hyperparameters (mean and sd for a lognormal prior).
sd_rr_hps	variance in site recruitment rates hyperparameters (shape and rate for a Gamma prior).

Value

an object of class `fahb_problem`

Examples

```
fahb_problem()
```

forecast

Generate probabilistic forecasts of trial recruitment

Description

Generate probabilistic forecasts of trial recruitment

Usage

```
forecast(problem, n_sims = 10^4, overwrite = FALSE)
```

Arguments

problem	an object of class <code>fahb_problem</code> .
n_sims	number of replicates to use in the simulation.
overwrite	boolean indicating if we want to overwrite any simulation data currently held (defaults to <code>FALSE</code>).

Value

an object of class fahb_problem.

Examples

```
problem <- fahb_problem()
problem <- forecast(problem, n_sims = 10^3)
```

plot.fahb_analysis *Plot posterior distributions from a fahb analysis*

Description

Takes an object of class fahb_analysis and plots the posterior distributions of the predicted time for the trial to recruit and of the three model parameters.

Usage

```
## S3 method for class 'fahb_analysis'
plot(x, ...)
```

Arguments

x object of class fahb_analysis as produced by fahb_analysis().
... further arguments passed to or from other methods.

Value

no return value, called for side effects.

plot.fahb_design *Plot operating characteristics of fahb designs*

Description

Takes an object of class fahb_design and plots the estimated operating characteristics of decision rules - based on standard progression criteria, an approximate Bayesian analysis, or both.

Usage

```
## S3 method for class 'fahb_design'
plot(x, ...)
```

Arguments

x object of class fahb_design as produced by fahb_design().
... further arguments passed to or from other methods.

Value

no return value, called for side effects.

`print.fahb_analysis` *Print a fahb analysis object*

Description

The default print method for a fahb_analysis object.

Usage

```
## S3 method for class 'fahb_analysis'  
print(x, ...)
```

Arguments

x object of class fahb_analysis as produced by fahb_analysis().
... further arguments passed to or from other methods.

Value

no return value, called for side effects.

`print.fahb_design` *Print a fahb design object*

Description

The default print method for a fahb_design object.

Usage

```
## S3 method for class 'fahb_design'  
print(x, coarse = TRUE, ...)
```

Arguments

x	object of class <code>fahb_design</code> as produced by <code>fahb_design()</code> .
coarse	binary indicator that only a coarse subset of all decision rules should be printed. Defaults to TRUE.
...	further arguments passed to or from other methods.

Value

no return value, called for side effects.

Index

`check_priors`, [2](#)

`fahb_analysis`, [3](#)

`fahb_design`, [4](#)

`fahb_problem`, [4](#)

`forecast`, [5](#)

`plot.fahb_analysis`, [6](#)

`plot.fahb_design`, [6](#)

`print.fahb_analysis`, [7](#)

`print.fahb_design`, [7](#)